



SETTING PROCEDURE FOR TEMPERATURE UNIT ON RKC CB500 CONTROLLER (CELCIUS AND FAHRENHEIT)

Procedure

* Read note A before steps 3 - 7 - 10 - 13

- 1) Press "SET" for 3 seconds "ArU" appears.
- 2) Press "SET" repeatedly until "LCK" appears.
- 3) With (\blacktriangle, ∇) keys, adjust value to 1000.
- 4) Press "**SET**" button for 3 seconds.
- 5) Hold simultaneously "SET" and "RS" for 3 seconds. "Cod" appears.
- 6) Press "SET" repeatedly up to "SL2" parameter.
- 7) With (\blacktriangle , ∇) keys, adjust value to "0010" for Celsius or "0011" for Fahrenheit and press "SET".
- 8) Hold "SET" and "RS" for 3 seconds.
- 9) Press "SET".
- 10) With (▲,▼) keys, adjust value to:
 "0043" for Celsius adjustment;
 "0110" for Fahrenheit adjustment;
- 11) Hold "SET" for 3 seconds. "ArU" appears.
- 12) Press "SET" repeatedly until "LCK" appears.
- 13) With (▲,▼) keys, adjust value to "0111".
- 14) Press "SET" for 3 seconds.

Important : Make sure RO stops by itself at desired temperature during first wash cycle.

*Note A : The most orange figure is the one that will change. Press "RS" to change the location of the digit to change.