

Safety Data Sheet



Item Code: CDLBM-15P
SAP #: 7300010098
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

1. Identification

Product identifier used on the label: CDL BRICK MORTAR

Other means of identification:

Synonyms: None

Recommended use of the chemical and restrictions on use:

Recommended use: Refractory insulation

Restrictions on use: Uses other than recommended use.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

Allied Mineral Products, LLC

2700 Scioto Parkway

Columbus, OH 43221

Telephone: (614)-876-0244

E-Mail of person responsible for SDS:

sdsinfo@alliedmin.com

Allied Mineral Products (Tianjin) Co., Ltd.

Address: No.2 Yanshan Road, TMHT Development Area,

Tianjin, 300459, China

Cell: +(86)22 2521 0378

Fax: +(86)22 2521 0375

Allied Mineral Products Europe B.V.

Energieweg 5 4691 SE

Tholen, Netherlands

Telephone: +31-166 601200

E-mail van de verantwoordelijke voor

veiligheidsbladen: sdsinfo@alliedmin.com

Allied Mineral Products South Africa (Pty) Ltd.

Crocker Road Wadeville Ext. 4

Wadeville Ext. 4

Germinston, 1407

South Africa

Telephone: +27-11-902-6930

Allied Refractory Products India Pvt. Ltd.

SM-5 Bol, G.I.D.C.

b/h Tata Nano, Tal.: Sanand

Dist.: Ahmedabad, Gujarat 382170, India

Telephone: +91-2717-616800

Fabricados no Brasil para Allied Mineral Products, Inc.

De Togni S/A Materiais Refratarios

Telephone: +55-35-2101-2222

Allied Mineral Products Rus LLC

423601, Russia, Republic of Tatarstan,

Yelabuga Region, City of Yelabuga,

Territory of SEZ "Alabuga",

Street Sh-2, Structure 5/12, Building 2, Facility 8

Phone: +7(85557)5-26-07;

Fax: +7(85557)5-26-06

Fabricado en Chile para Allied Mineral Products, Inc.

Por Refratarios lunge Ltda.

Telephone: (56-2) 2745-3613

Emergency phone number:

CHEMTREC: (800) 424-9300

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard
Symbols:



GHS Classification:

Serious Eye Damage/Eye Irritation Category 1

Carcinogenicity Category 1A

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Skin Corrosion/Irritation Category 2

Signal Word:

Danger

Hazard Statements:

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H350 - May cause cancer.

H370 - Causes damage to organs.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Response:

P302+P352 - If on skin: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see Sections 4 to 8 on this SDS and any additional information on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

Disposal:

P501 - Dispose of contents/container to a suitable disposal site in accordance with local/national/international regulations.

Hazards not otherwise classified:

This product also contains nuisance dust. Although the nuisance dust contains no additional hazards, appropriate PPE should be used.

Cancer Statement:

Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1600°F) it can change to a form of crystalline silica known as tridymite, and if crystalline silica (quartz) is heated to more than 1470°C (2680°F), it can change to a form of crystalline silica known as cristobalite. Crystalline silica as tridymite and cristobalite are more fibrogenic than crystalline silica as quartz. IARC has listed crystalline silica from occupational sources as a Group I carcinogen. A Group I carcinogen is one in which there is sufficient evidence for carcinogenicity in humans. NTP has listed crystalline silica as reasonably anticipated to be a carcinogen.

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Silica, Crystalline quartz (non-respirable)	None	14808-60-7	10 - 30
Proprietary Ingredient #20	None	Trade Secret #20	10 - 30
Kaolin	None	1332-58-7	5 - 10
Silica, Crystalline quartz (respirable)	None	14808-60-7	0.5 - 1.5

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Silica, Cristobalite (non-respirable)	None	14464-46-1	0.1 - 1
Non Hazardous components *	Not applicable	Not applicable	Not applicable

* The non hazardous ingredients percentage includes the components that are hazardous but below the threshold for GHS classification. In the case where there are no hazardous components, the percentage of non hazardous ingredients will be 100%.

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
Eye Contact:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
Skin Contact:	Wash with soap and water. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.
Ingestion:	Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute.
Most important symptoms/effects, acute and delayed:	Causes skin irritation Causes serious eye damage Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.
Indication of immediate medical attention and special treatment needed, if necessary:	Specific treatment (see Sections 4 to 8 on this SDS and any additional information on this label). Immediately call a poison center or doctor/physician.

5. Fire-fighting measures

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use methods suitable to fight surrounding fire.

Unsuitable extinguishing media: None Known

Specific hazards arising from the chemical: Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Use process enclosures to control the level of dust in the air.

Hazardous combustion products: Toxic gases, Carbon dioxide, Carbon monoxide, Toxic fumes.

Special protective equipment and precautions for fire-fighters: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Methods and materials for containment and cleaning up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. Handling and storage

Precautions for safe handling: Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Wash thoroughly after handling Do not get in eyes, on skin and clothing Remove contaminated clothing and wash before

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

reuse Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Minimize dust generation and accumulation Mildly irritating material. Avoid unnecessary exposure.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions: Keep away from heat, sparks, and flame

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Silica, Crystalline quartz (non- respirable)	0.05 mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	Not established	50 mg/m ³ IDLH (respirable dust)
Kaolin	total dust: 15 mg/m ³ TWA; respirable fraction: 5 mg/m ³ TWA	respirable dust: 2 mg/m ³ TWA (The value is for total dust containing no	Not established	Not established
Silica, Crystalline quartz (respirable)	0.05 mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	Not established	50 mg/m ³ IDLH (respirable dust)
Silica, Cristobalite (non-respirable)	0.05 mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	Not established	25 mg/m ³ IDLH (respirable dust)

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Facilities storing or using this material should be equipped with an eyewash and safety shower.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Ventilation is required to maintain operator exposure below published exposure limits.

Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection:

Respiratory protection will be required when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Wear a NIOSH approved respirator if any exposure is possible. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Recommend chest X-rays and yearly vital capacity tests for employees regularly exposed to silica for early detection of silicosis. Comply with all guidelines for crystalline silica exposure.

Respirator Type(s):

If it is not possible to reduce airborne exposure levels to below the exposure limits with ventilation, use the table below to assist you in selecting respirators that will reduce personal exposures to below the exposure limits.

The assigned protection factor (APF) is the minimum anticipated level of protection provided by each type of respirator worn in accordance with an adequate respiratory protection program. For example, an APF of 10 means that the respirator should reduce the airborne concentration of a particulate by a factor of 10, so that if the workplace concentration of a particulate was 150 ug/m³, then a respirator with an APF of 10 should reduce the concentration of particulate to 15 ug/m³.

Assigned Protection Factor	Type of Respirator
10	Any air-purifying elastomeric half-mask respirator equipped with appropriate type of particulate filter. Appropriate filtering facepiece respirator. Any air-purifying full facepiece respirator equipped with appropriate type of particulate filter. Any negative pressure (demand) supplied-air respirator equipped with a half-mask.
25	Any powered air-purifying respirator equipped with a hood or helmet and a high efficiency (HEPA) filter. Any continuous flow supplied-air respirator equipped with a hood or helmet.
50	Any air-purifying full facepiece respirator equipped with N-100, R-100, or P-100 filter(s).

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

	Any powered air-purifying respirator equipped with a tight-fitting facepiece (half or full facepiece) and a high-efficiency filter. Any negative pressure (demand) supplied-air respirator equipped with a full facepiece. Any continuous flow supplied-air respirator equipped with a tight-fitting facepiece (half or full facepiece). Any negative pressure (demand) self-contained respirator equipped with a full facepiece.
1000	Any pressure-demand supplied-air respirator equipped with a half-mask.

Eye protection:

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

Wear goggles and a Face shield

Skin protection:

Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield

Gloves:

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and type of use. Gloves should be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Other protective equipment:

Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield

Wear goggles and a Face shield

General hygiene conditions:

Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Physical state:	Granular, wet material
Color:	Colorless White
Odor:	No Odor
Odor Threshold:	No data available
pH:	Not applicable
Melting point/freezing point (°C):	
Melting Point (°C):	> 2000 °F (> 1100 °C)
Freezing point (°C):	Not applicable
Initial boiling point and boiling range (°C):	Not applicable
Flash Point (°C):	Not applicable
Evaporation Rate:	No data available
Flammability (solid, gas):	Non-flammable
Upper/lower flammability or explosive limits:	
Upper flammability or explosive limits:	Not applicable
Lower flammability or explosive limits:	Not applicable
Vapor pressure:	Not applicable
Vapor density:	Not applicable
Relative density:	2 to 3.5 g/cc
Solubility(ies):	< 3%
Partition coefficient: n-octanol/water:	Not applicable
Auto-ignition temperature (°C):	Not applicable
Decomposition temperature (°C):	Not applicable
Viscosity:	Not applicable
Volatile Organic Chemicals:	Not established
Bulk Density:	No data available

10. Stability and reactivity

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Reactivity:	Not expected to be reactive
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	None expected under standard conditions of storage
Conditions to avoid (e.g., static discharge, shock, or vibration):	Contamination
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Toxic gases, Carbon dioxide, Carbon monoxide, Toxic fumes.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Skin contact, Eye contact, Eye contact, Skin contact, Ingestion, Inhalation
---	---

Symptoms related to the physical, chemical and toxicological characteristics:	Causes skin irritation Causes serious eye damage Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.
---	---

Additional Information:	<p>SILICOSIS- The major concern is silicosis, caused by the inhalation and retention of respirable crystalline silica dust. Silicosis can exist in several forms, chronic (or ordinary), and accelerated (or acute). Chronic or Ordinary Silicosis is the most common form of silicosis, and can occur after many years of exposure to relatively low levels of airborne respirable crystalline silica dust. It is further defined as either simple or complicated silicosis. Simple Silicosis is characterized by lung lesions (shown as radiographic opacities) less than 1 centimeter in diameter, primarily in the upper lung zones. Often, simple silicosis is not associated with symptoms, detectable changes in lung function, or disability. Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF). Complicated Silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than 1 centimeter in diameter. Although there may be no symptoms associated with complicated silicosis or PMF, the symptoms, if present, are shortness of breath, wheezing, cough, and sputum production. Complicated silicosis or PMF may lead to death. Advanced complicated silicosis or PMF can result in heart disease secondary to the lung disease</p>
-------------------------	---

Safety Data Sheet



Item Code: CDLBM-15P

Revision Date: 06 February 2025

Revision Number: 1

Replaces: None

CDL BRICK MORTAR

(corpulmonale). Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; the lung lesions can appear within five (5) years of the initial exposure. The progression can be rapid. Accelerated Silicosis is similar to chronic or ordinary silicosis, except that the lung lesions appear earlier and the progression is more rapid. Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough, and weight loss. Acute silicosis is fatal.

SCLERODERMA- There is evidence that exposure to respirable crystalline silica or that the disease silicosis is associated with the increased incidence of scleroderma, an immune system disorder manifested by a fibrosis (scarring) of the lungs, skin, and other internal organs. Recently, the American Thoracic Society noted that "there is persuasive evidence relating scleroderma to occupational silica exposures in settings where there is appreciable silicosis risk". The following may be consulted for additional information on silica, silicosis, and scleroderma (also known as progressive systemic sclerosis): Occupational Lung Disorders, Third Edition, Chapter 12, entitled "Silicosis and Related Diseases", Parkes, W. Raymond (1994). "Adverse Effects of Crystalline Silica Exposure", American Journal of Respiratory and Critical Care Medicine, Volume 155, pp. 761-765 (1997).

TUBERCULOSIS- Individuals with silicosis are at increased risk to develop tuberculosis, if exposed to persons with tuberculosis. The following may be consulted for further information: Occupational Lung Disorders, Third Edition, Chapter 12, entitled "Silicosis and Related Diseases", Parkes, W. Raymond (1994). "Adverse Effects of Crystalline Silica Exposure", American Journal of Respiratory and Critical Care Medicine, Volume 155, pp. 761-765 (1997).

NEPHROTOXICITY- There are several recent studies suggesting that exposure to respirable crystalline silica or that the disease silicosis is associated with the increased incidence of kidney disorders. The

Safety Data Sheet



Item Code: CDLBM-15P

Revision Date: 06 February 2025

Revision Number: 1

Replaces: None

CDL BRICK MORTAR

following may be consulted for additional information on silica, silicosis, and nephrotoxicity: Occupational Lung Disorders, Third Edition, Chapter 12, entitled "Silicosis and Related Diseases", Parkes, W. Ramond (1994). "Further evidence of human silica nephrotoxicity in occupationally exposed workers", British Journal of Industrial Medicine, Vol 50, No. 10, pp. 907-912 (1993). "Adverse Effects of Crystalline Silica Exposure", American Journal of Respiratory and Critical Care Medicine, Volume 155, pp. 761-765 (1997).

ARTHRITIS- There are recent studies suggesting that exposure to respirable crystalline silica or that the disease silicosis is associated with the increased incidence of arthritis. The following may be consulted for additional information on silica exposure and arthritis: American Journal of Industrial Medicine, Volume 35, pp. 375-381 "Connective Tissue Disease and Silicosis", Rosenman KD; Moore-Fuller M.; Reilly MJ. (1999). Environmental Health Perspective, Volume 107, pp. 793802 "Occupational Exposure to Crystalline Silica and Autoimmune Disease", Parks CG, Conrad K, Cooper GS. (1999).

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.
Skin Contact:	Can cause severe irritation, defatting, and dermatitis. Irritation effects may last for hours or days but will not likely result in permanent damage.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")
Eye Contact:	Causes serious eye damage
Sensitization:	None Known
Reproductive and Developmental Toxicity:	No data available
Carcinogenicity:	Classification has been based on toxicological information of the components in Section 3.
STOT-single exposure:	Classification has been based on toxicological information of the components in Section 3.
STOT-repeated exposure:	Classification has been based on toxicological information of the components in Section 3.

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Aspiration hazard: Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Proprietary Ingredient #20	ORAL LD50 Rat 1960 mg/kg	DERMAL LD50 Rabbit 4640 mg/kg	No data available
Kaolin	ORAL LD50 Rat > 5000 mg/kg	DERMAL LD50 Rat > 5000 mg/kg	No data available

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Silica, Crystalline quartz (non- respirable)	N	Yes	Yes
Silica, Crystalline quartz (respirable)	N	Yes	Yes
Silica, Cristobalite (non-respirable)	N	Yes	Yes

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Dusts of as-manufactured refractory product have a low order of aquatic toxicity, are insoluble, and are not very mobile. Based upon this information, it is not believed to be a significant threat to the environment if accidentally released on land or into water. However, dust and material generated during maintenance and tear-out operations may be contaminated with other hazardous substances (e.g., metals, respirable crystalline silica, alkaline materials). Evaluation of dust and material from specific processes should be performed to determine if an environmental threat exists in the case of release.

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Proprietary Ingredient #20	Trade Secret #20	No data available	No data available	Aquatic LC50 96 H BRACHYDANIO RERIO 3185 MG/L

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Persistence and degradability:	Not applicable
Bioaccumulative potential:	Not applicable
Mobility in soil:	Not applicable
Other adverse effects (such as hazardous to the ozone layer):	None Known

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

The as-manufactured refractory product or refractory dust is not considered a hazardous waste. Dust and material generated during use, maintenance and tear-out operations may be contaminated with other hazardous substances (e.g., metals, alkaline materials) from a particular application. Additionally, the spent refractory could contain reaction products not originally present in the supplied refractory material. Contaminants or reaction products have the potential to cause the refractory waste to exhibit hazardous waste characteristics. It is the responsibility of the user to consult applicable regulations prior to disposal of any industrial product to ensure waste disposal compliance. Waste analysis and characterization may be necessary to determine proper waste disposal. Waste Management: Dusts could contain respiratory hazards. To prevent waste materials becoming airborne during waste generation, storage, transportation, and disposal, proper dust control measures are recommended.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

UN number:	Not Regulated for Transport
UN Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group, if applicable:	Not applicable

International carriage of dangerous goods by sea (IMDG/IMO):

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

UN number: Not Regulated for Transport

UN Proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group, if applicable: Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not Regulated for Transport

UN Proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group, if applicable: Not applicable

Environmental hazards (e.g., Marine pollutant (Yes/No)): No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): No data available

Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises: No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components in this product are on the TSCA Inventory.

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Regulated Components:

Chemical Name	CAS #	CERCLA	Sara EHS	Sara 313	U.S. HAP
Silica, Crystalline quartz (non-respirable)	14808-60-7	N	N	N	N
Proprietary Ingredient #20	Trade Secret #20	N	N	N	N
Kaolin	1332-58-7	N	N	N	N
Silica, Crystalline quartz (respirable)	14808-60-7	N	N	N	N
Silica, Cristobalite (non-respirable)	14464-46-1	N	N	N	N

Chemical Name	CAS #	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Silica, Crystalline quartz (non-respirable)	14808-60-7	Yes	N	N	N
Proprietary Ingredient #20	Trade Secret #20	N	N	N	N
Kaolin	1332-58-7	N	N	N	N
Silica, Crystalline quartz (respirable)	14808-60-7	Yes	N	N	N
Silica, Cristobalite (non-respirable)	14464-46-1	Yes	N	N	N

Safety Data Sheet



Item Code: CDLBM-15P
Revision Date: 06 February 2025
Revision Number: 1
Replaces: None

CDL BRICK MORTAR

Chemical Name	CAS #	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Silica, Crystalline quartz (non- respirable)	14808-60-7	N	Yes	Yes	N	Yes
Proprietary Ingredient #20	Trade Secret #20	N	N	N	N	N
Kaolin	1332-58-7	N	Yes	Yes	N	Yes
Silica, Crystalline quartz (respirable)	14808-60-7	N	Yes	Yes	N	Yes
Silica, Cristobalite (non- respirable)	14464-46-1	N	Yes	Yes	N	Yes

16. Other information, including date of preparation or last revision.

SDS Prepared by: Environmental, Health & Safety Compliance

Revision Date: 06 February 2025

Revision Number: 1

Reason for revision: New GHS Format

Abbreviations and acronyms: CAS = Chemical Abstract Service
DNEL= Derivative No Effect Level
EC= European Community
EINECS = European Inventory of Existing Chemical Substances
MSHA = Mine Safety Health Administration
NIOSH = National Institute of Occupational Safety & Health
OEL = Occupational Exposure Limit
PBT= Persistent, Bioaccumulative, Toxic
PNEC= Predicted No Effect Concentration
SCOEL= Scientific Committee on Occupational Exposure Limits
TLV = Threshold Limit Value
TWA= Time Weighted Average
vPvB= Very Persistent, Very Bioaccumulative
Wt.% = Weight Percent

Disclaimer: All information provided here is based on data believed to be reliable.
However, THE INFORMATION AND THE PRODUCT ARE PROVIDED

Safety Data Sheet



Item Code: CDLBM-15P

Revision Date: 06 February 2025

Revision Number: 1

Replaces: None

CDL BRICK MORTAR

WITHOUT ANY REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO REPRESENTATIONS AND WARRANTIES REGARDING ACCURACY OR CORRECTNESS, THE EFFECTS OF USING THE PRODUCT, THE RESULTS TO BE OBTAINED, FITNESS FOR A PARTICULAR PURPOSE, OR THE SAFETY OR TOXICITY OF THE PRODUCT. It is the users' responsibility to determine the safety, toxicity, and suitability for their use of the product and to comply with all applicable statutes and regulations. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control. For this and other reasons, Allied Mineral Products, LLC. does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of, relating to, or in any way connected with the handling, storage, use, or disposal of this product. This SDS is not intended as a license to operate under, or a recommendation to infringe on, any patents. Appropriate warnings and safe handling instructions should be provided to handlers and users.